

1" Impactool™ with extended anvil





The 631L Impactool delivers exceptional power and rugged durability in a convenient, easy-to-use package. It is the perfect tool for the most demanding applications, such as truck and bus service, construction and agricultural equipment maintenance, tire changing, as well as the MRO market.

- 4 300 Nm (3 172 ft-lb) of maximum torque.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Swinging hammer impact mechanism is well-suited to wide range of air pressures.
- Powerful 6-vane motor delivers superior performance.
- Chemical-resistant boots absorb shocks and protect the tool from damage.
- Ergonomic auxiliary handle provides excellent maneuverability.
- 4-position power regulator and forward/reverse control.



Specifications at 6,2 bar (90 psi)

 Part Number
 631L

 Ordering number
 80183171

 Drive size (square)
 1 in

 Drive length
 8 in / 200 mm

PERFORMANCE

 Working torque
 200 - 2 500 ft-lb / 271 - 3 390 Nm

 Maximum torque
 3 172 ft-lb / 4 300 Nm

 Recommended fastener size
 2.1/4 in / M55

 Free speed
 3 500 rpm

 Impacts per minute
 700

AIR SYSTEM

Air Inlet (NPTF) 1/2 in
Minimum hose size 1/2 in / 13 mm
Average air consumption 15 CFM / 427 L/min
Air consumption at load 56,0 CFM / 1 585 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744) 108,4 / 119,4 dB(A)
Vibration level / measurement uncertainty (ISO28927) 12,7 / 2,5 m/s²

WEIGHT & DIMENSIONS

 Tool weight
 36,5 lb / 16,6 kg

 Tool length
 24,6 in / 624 mm

 Shipping weight
 40,0 lb / 18,2 kg

 Shipping dimensions (L x W x H)
 270 x 697 x 170 mm

 UPC / EAN code
 6 63023 03657 1

 Origin
 Made in China

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.





631L ACCESSORIES



SK8M4L

81287419

1" Impact socket set (4 pcs) (27, 30, 32 and 33 mm)



Impact sockets

For the complete range, see our accessory catalogue.



327-EU

01343771

10 mm high-speed tire buffer



327LS

01371699

7/16" tire buffer



IB8NMC4

88103312

IBN/IBS Series nipple, 1/2" male thread, 8 mm bore (ISO6150B / MIL-C4109)



IB11NMC4

25014036

IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-C4109)



77NMC4

88104096

7N7/7S7 Series nipple, 1/2" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



105-LBK1

04616090

Lubricant kit for Impactools™ with metal housing



10**Z**4

03875671

Oil, Class 1, no. 10, 0,12 L



105-4T-6

04618930

Grease for Impactool hammer mechanism (6 tubes)



Lubricants

For the complete range, see our accessory catalogue.



631L-TK1

Motor service kit



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

