





The 290-EU Impactool delivers exceptional power and rugged durability in a convenient, easy-to-use package. It is the perfect tool for the most demanding applications, such as truck and bus service, construction and agricultural equipment maintenance, tire changing, as well as the MRO market.

- 2 169 Nm (1 600 ft-lb) of maximum torque.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Ingersoll Rand JumboHammer impact mechanism is the simplest and the most durable and longest life mechanism in the industry.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- · Powerful 6-vane motor delivers superior performance.
- Ergonomic handle design and textured finish provide a secure and comfortable grip.
- Ergonomic auxiliary handle provides excellent maneuverability.
- Through-handle exhaust directs air away from the operator.

### Specifications at 6.2 bar (90 psi)

Part Number	290-EU
Ordering number	01343177
Drive size (square)	1 in
Other available versions: - 150 mm (6") extended anvil	290-6-EU

### PERFORMANCE

Working torque Maximum torque Recommended fastener size Free speed Impacts per minute

#### AIR SYSTEM

Air Inlet (NPT) Minimum hose size Average air consumption Air consumption at load

NOISE & VIBRATION Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927)

#### WEIGHT & DIMENSIONS

Tool weight Tool length Shipping weight Shipping dimensions (L x W x H) UPC / EAN code Origin 1 600 ft-lb / 2 169 Nm 1-1/4 in / M32 6 000 rpm 800

150 - 1 000 ft-lb / 203 - 1 356 Nm

1/2 in 3/4 in / 19 mm 10 CFM / 283 L/min 60 CFM / 1 699 L/min

> 104.6 / 117.6 dB(A) 22.7 / 2.6 m/s<sup>2</sup>

21.9 lb / 9.93 kg 9.75 in / 248 mm 25.3 lb / 11.5 kg 320 x 380 x 160 mm 6 63023 00385 6 Assembled in the USA

(6

# www.ingersollrandproducts.com





SK8M4L



81287419 1" Impact socket set (4 pcs) (27, 30, 32 and 33 mm)



### Impact sockets

For the complete range, see our accessory catalogue.



2934-366 03441508 Horizontal hanger



33304 91488205 Hose whip, 1/2" NPT, 13 mm inside diameter, 30 cm (1 ft)



IB11NMC4

25014036 IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-C4109)

**Quick Release Couplings** For the complete range, see our

accessory catalogue.

105-LBK1 04616090 Lubricant kit for Impactools<sup>™</sup> with metal housing



0

105-4T-6 04618930 Grease for Impactools hammer mechanism (6 tubes)

290-TK2 03866613 Motor service kit



E87H 16586570 1" Extension 175 mm

#### Socket retainer rings

For the complete range, see our accessory catalogue.

290-EU

ACCESSORIES





#### **IB8NMC4** 88103312

IBN/IBS Series nipple, 1/2" male thread, 8 mm bore (ISO6150B / MIL-C4109)

#### 77NMC4

10Z4

03875671

88104096 7N7/7S7 Series nipple, 1/2" male thread, 7.2 mm bore (EURO 7.2 - 7.4)

#### Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



Lubricants

Oil, Class 1, no. 10, 0.12 L

For the complete range, see our accessory catalogue.

# www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.





