



Suction Pump



The CD150M pump offers flow rates of up to 8,666l/min (520 m³/hr) and has the capability of handling solids up to 75mm (3") in diameter. The CD150M is able to automatically prime to 8.5m (28ft) of suction lift. Indefinite dry-running is possible with the exclusive Godwin liquid bath mechanical seal design. Solids handling, dry running and portability make the CD150M the perfect choice for dewatering, sewage bypass and water transfer applications.



Suction Pump	
Model	CD150M
Max Pressure	4.8 bar (70psi)
Max Suction Pressure	4.0 bar (58psi)
Max Soft Solids Handling	75mm (3")
Flange Suction Side	150mm (6")
Flange Discharge Side	150mm (6")
Engine	Electric start radiator cooled diesel
Frame	Pump in a banded box canopy sound attenuated enclosure with forklift pockets and central lifting eye
Safety Features	Fitted with chawlyne valve, spark arrestor, battery isolator, external E-stop button



For more information on how Fisher Offshore can add value to your offshore operations visit www.fisheroffshore.com or contact one of our specialist consultants at info@fisheroffshore.com or call +44 (0) 1651 87 39 32
 Fisher Offshore, North Meadows, Oldmeldrum, Aberdeenshire, Scotland AB51 0GQ