

2920B1-EU

3/4" ImpactoolTM



The 2920B1-EU is Ingersoll Rand's most durable Impactool and is designed for intensive and heavy-duty industrial maintenance and production applications.

- 949 Nm (700 ft-lb) of maximum torque in reverse.
- The Ingersoll Rand impact mechanism with proprietary advanced metallurgy provides the ultimate in durability and reliability.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- Steel hammercase provides excellent durability under the toughest use.
- Powerful 6-vane motor delivers superior performance.
- Ergonomic auxiliary handle provides excellent maneuverability.
- Feather-touch trigger allows precise delivery of power and speed.
- Wide range of power regulator settings helps adjusting the power to the application.

Specifications at 6.2 bar (90 psi)

Part Number 2920B1-EU
Ordering number 01338045
Drive size (square) 3/4 in
Socket retainer type through-hole
Other available versions:

- 3/4" square drive, right-angle head 2920B9-EU

PERFORMANCE

 Working torque in forward
 250 - 800 ft-lb / 339 - 1 085 Nm

 Maximum torque in forward
 1 100 ft-lb / 1 491 Nm

 Working torque in reverse
 250 - 800 ft-lb / 339 - 1 085 Nm

 Maximum torque in reverse
 1 100 ft-lb / 1 491 Nm

 Recommended fastener size
 1 -1/4 in / M32

 Free speed
 5 000 rpm

 Impacts per minute
 950

AIR SYSTEM

Air Inlet (NPT)3/8 inMinimum hose size1/2 in / 13 mmAir consumption at load36 CFM / 17 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744) 87.9 / 100.9 dB(A)
Vibration level / measurement uncertainty (ISO28927) 19.9 / 6.6 m/s²

WEIGHT & DIMENSIONS

 Tool weight
 13.2 lb / 5.98 kg

 Tool length
 12.5 in / 318 mm

 Shipping weight
 0 lb / 0 kg

 Shipping dimensions (L x W x H)
 245 x 560 x 165 mm

 UPC / EAN code
 6 63023 09623 0

 Origin
 Made in USA







2920B1-EU

ACCESSORIES



SK6M6L 81287401

3/4" Impact socket set (6 pcs) (24, 27, 30, 32, 33 and 36 mm)



E63H

16586521

3/4" Extension 75 mm



E67H

16586539

3/4" Extension 175 mm



Impact sockets

For the complete range, see our accessory catalogue.



910-366

03403896

Horizontal hanger



BMDLN-8

17023755

Cable balancer, 6-8 kg, 2.5 m (8-1/4 ft)



33204

91486357

Hose whip, 3/8" NPT, 10 mm inside diameter, 30 cm (1 ft)



IB8NMC3

88103304

IBN/IBS Series nipple, 3/8" male thread, 8 mm bore (ISO6150B / MIL-C4109)



77NMC3

88104088

7N7/7S7 Series nipple, 3/8" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



RH-12

92536051

PVC hose, 13 mm inside diameter, 30 m



CO-1518

56753122

Hose clamps, 15-18 mm outside diameter, 100 pcs



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



105-LBK1

04616090

Lubricant kit for Impactools™ with metal housing



10Z4

03875671

Oil, Class 1, no. 10, 0.12 L



105-4T-6

04618930

Grease for Impactools hammer mechanism (6 tubes)



Lubricants

For the complete range, see our accessory catalogue.



2920B-TK2

03803095

Motor service kit



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

