





The classic 212 is one of the most popular Impactools[™] in its class. It provides plenty of power and rugged durability in a convenient easy-to-use package.

- 244 Nm (180 ft-lb) of maximum torque.
- Ingersoll Rand JumboHammer impact mechanism is the simplest and the most durable and longest life mechanism in the industry.
- Pressure-feed lubrication system automatically greases the impact mechanism for increased durability and reliability.
- The small size of this tool will allow greater access to tight spaces.
- Wide range of power regulator settings helps adjusting the power to the application.
- Through-handle exhaust directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number Ordering number Drive size (square)

PERFORMANCE

Working torque Maximum torque

Recommended fastener size Free speed Impacts per minute

AIR SYSTEM

Air Inlet (NPTF) Minimum hose size Average air consumption Air consumption at load

NOISE & VIBRATION

Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927)

WEIGHT & DIMENSIONS

Tool weight Tool length Shipping weight Shipping dimensions (L x W x H) UPC / EAN code Origin 20 - 125 ft-lb / 27 - 170 Nm 180 in-lb / 244 Nm 7/16 in / M11 10 000 rpm

212

3/8 in

1 500

01197003

1/4 in 3/8 in / 10 mm 2.5 CFM / 71 L/min 11.0 CFM / 311 L/min

> 97.5 / 110.5 dB(A) 6.5 / 1.0 m/s²

2.89 lb / 1.31 kg 6.0 in / 152 mm 3.41 lb / 1.55 kg 200 x 210 x 80 mm 6 63023 00004 6 Made in China

CE

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.







SK3M10 81287344 2/8" Impact socket set (10 pc

3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



1901-366 03670163 Horizontal hanger



212-BOOT 45505344 Protective tool boot



33104-45 92938760 Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1.5 ft)



77NMC2 88104070 7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



For the complete range, see our accessory catalogue.

Filters, regulators, lubricators



105-LBK1 04616090 Lubricant kit for Impactools[™] with metal housing



0

105-4T-6 04618930 Grease for Impactools hammer mechanism (6 tubes)

212-TK2 03866522 Motor service kit





BMDS-2 92842152

Impact sockets

accessory catalogue.

For the complete range, see our

Cable balancer, 1-2.5 kg, 2 m (6-1/2 ft)



IB6NMC2 88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)

Quick Release Couplings

For the complete range, see our accessory catalogue.



10Z4 03875671 Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



