

## 2135XP 1/2" Impactool<sup>TM</sup>





Perfect for any maintenance or repair application, the 2135XP delivers plenty of power and superior control, along with unmatched reliability that comes from more than a century of proven engineering and innovation.

- 935 Nm (690 ft-lb) of maximum torque in reverse.
- Ingersoll Rand TwinHammer impact mechanism is the strongest, most durable and longest life mechanism in the industry.
- Powerful reverse-bias 6-vane motor delivers even more power in reverse.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- 4-position power regulator in forward helps adjusting the power to the application.
- One-hand forward/reverse switch for easy operation.
- 360° swivel inlet helps eliminating twisted hoses.
- Silenced through-handle exhaust reduces the noise
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.

## Specifications at 6,2 bar (90 psi)

Part Number 2135XP 45606704 Ordering number Drive size (square) 1/2 in Available versions: 2135XP+SK - kit with 10 short sockets 2135XP+SK4M3L

### PERFORMANCE

- kit with 3 long sockets

Working torque in forward 50 - 502 ft-lb / 68 - 680 Nm Maximum torque in forward 531 ft-lb / 720 Nm Working torque in reverse 579 ft-lb / 785 Nm 690 ft-lb / 935 Nm Maximum torque in reverse Recommended fastener size 9/16 in / M14 Free speed 8 900 rpm Impacts per minute 1 250

### AIR SYSTEM

Air Inlet (NPTF) 1/4 in 3/8 in / 10 mm Minimum hose size 5.0 CFM / 142 L/min Average air consumption 24,0 CFM / 680 L/min Air consumption at load


### **NOISE & VIBRATION**

Impacting sound pressure / power (ISO15744) 95,5 / 106,5 dB(A) Free speed sound pressure / power (ISO15744) 90,4 / 101,4 dB(A) Vibration level / measurement uncertainty (ISO28927) 13,3 / 4,6 m/s<sup>2</sup>

### WEIGHT & DIMENSIONS

Tool weight 4,20 lb / 1,90 kg Tool dimensions (L x W x H) 187 x 69 x 183 mm Shipping weight 5,10 lb / 2,30 kg Shipping dimensions (L x W x H) 238 x 213 x 79 mm UPC / EAN code 6 63023 04796 6 Assembled in the USA Origin

### www.ingersollrandproducts.com







# 2135XP

### **ACCESSORIES**



SK4M3L

81287377

1/2" Impact socket set (3 pcs) (17, 19 and 21 mm)



**SK4M14** 

81287351

1/2" Impact socket set (14 pcs) (10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23 and 24 mm)



Impact sockets

For the complete range, see our accessory catalogue.



2131-366

04706388

Horizontal hanger



2135-BOOT

45505377

Protective tool boot



### **IB6NMC2**

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



### **Quick Release Couplings**

For the complete range, see our accessory catalogue.



115-LBK1

04616108

Lubricant kit for Impactools™ with composite housing



### 115-4T-6

04618948

Grease for Impactools with composite housing (6 tubes)



#### 2135-THK1

80119571

Impact mechanism service kit



### SK4M5L

81287369

1/2" Impact socket set (5 pcs) (17, 19, 21, 22 and 24 mm)



**SK4M18** 

81287385

1/2" Impact socket set (18 pcs) (10, 11, 13, 14, 17, 19, 21, 22, 24, 13L, 14L, 21L, 24L, 17L, 19L and 21L mm, extension 125 mm)



**4UA9** 

03070216

1/2" right-angle head (speed reduction: 25% torque output reduction: up to 50%)



**BMDS-4** 

92842087

Cable balancer, 2-4 kg, 2 m (6-1/2 ft)



2115-K284

45612637

Piped-away exhaust kit



**77NMC2** 

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10**Z**4

03875671

Oil, Class 1, no. 10, 0,12 L



### Lubricants

For the complete range, see our accessory catalogue.



2135-TK2

45535028

Motor service kit



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

