

# *122MAXH*

Hammer



The 122MAXH hammer provides best-in-class power, superior ergonomics and reduced vibration to maximize operator comfort and productivity. It is perfect for exhaust system work, bodyshop applications, scrapping rust, bolt and rivet cutting as well as metal panel cutting.

- Up to 3 500 blows per minute.
- Alloyed steel barrel and heat-treated piston ensures longer
- Vibration reduction technology significantly increases user comfort and productivity.
- Quick change retainer provides fast and easy chisel change.
- Rubber handle grip offers great operator comfort and protects from cold air.
- Variable-speed lever allows precise delivery of power and
- 360° swivel inlet helps eliminating twisted hoses.
- Through-handle exhaust directs air away from the operator.
- Tool also available as kit with: quick-change retainer and 5 chisels.

## Specifications at 6.2 bar (90 psi)

Part Number 122MAXH Ordering number Part Number (kit) 46816740 122MAXHK Ordering number (kit) 46816757 Shank type hexagonal 0.401 in / 10.2 mm Shank size

Other available versions:

- round shank 122MAX - round shank and chisels 122MAXK

#### PERFORMANCE

Piston bore 3/4 in / 19 mm Piston stroke 2-5/8 in / 67 mm Blows per minute 3 500

### AIR SYSTEM

Air Inlet (NPT) 1/4 in Minimum hose size 3/8 in / 10 mm Average air consumption 2.90 CFM / 82.1 L/min 2.93 CFM / 82.9 L/min Air consumption at load

#### **NOISE & VIBRATION**

94.7 / 105.7 dB(A) Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927) 7.5 / 2.8 m/s<sup>2</sup>

### WEIGHT & DIMENSIONS

4.0 lb / 1.8 kg Tool weight Tool dimensions (L x W x H) 10.4 x 2.2 x 6.9 in / 218 x 56 x 175 mm Shipping weight (tool only) 5.3 lb / 2.4 kg Shipping weight (kit) 8.1 lb / 3.7 kg Shipping dimensions (tool only) (L x W x H) 305 x 195 x 80 mm Shipping dimensions (kit) (L x W x H) 445 x 310 x 90 mm UPC / EAN code (tool only) 6 63023 10066 1 UPC / EAN code (kit) 6 63023 10065 4 Origin Made in Taiwan







# 122MAXH

## **ACCESSORIES**



116H-K5

92536093

Chisels, hexagonal shank, 10.2 mm (5 pieces)



116-66H

92684901

Chisel, hexagonal shank, 10.2 mm



116-70H

92684943

Chisel, hexagonal shank, 10.2 mm



116-87H

92684935

Chisel, hexagonal shank, 10.2 mm



116-88H

92684919

Chisel, hexagonal shank, 10.2 mm



116-89H

92684927

Chisel, hexagonal shank, 10.2 mm



9512

33104

91486330

45563749

Quick change retainer

diameter, 30 cm (1 ft)



**IB6NMC2** 

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



**77NMC2** 

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)

Hose whip, 1/4" NPT, 6 mm inside



**Quick Release Couplings** 

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10**Z**4

03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

