

122MAX

Hammer





The 122MAX hammer provides best-in-class power, superior ergonomics and reduced vibration to maximize operator comfort and productivity. It is perfect for exhaust system work, bodyshop applications, scrapping rust, bolt and rivet cutting as well as metal panel cutting.

- Up to 3 500 blows per minute.
- Alloyed steel barrel and heat-treated piston ensures longer life.
- Vibration reduction technology significantly increases user comfort and productivity.
- · Quick change retainer provides fast and easy chisel change.
- Rubber handle grip offers great operator comfort and protects from cold air.
- Variable-speed lever allows precise delivery of power and speed.
- 360° swivel inlet helps eliminating twisted hoses.
- Through-handle exhaust directs air away from the operator.
- Tool also available as kit with: quick-change retainer and 5 chisels.

Specifications at 6.2 bar (90 psi)

 Part Number
 122MAX

 Ordering number
 47124482

 Part Number (kit)
 122MAXK

 Ordering number (kit)
 47125869

 Shank type
 round

 Shank size
 0.401 in / 10.2 mm

Other available versions:
- hexagonal shank
- hexagonal shank and chisels

122MAXH

122MAXHK

PERFORMANCE

 Piston bore
 3/4 in / 19 mm

 Piston stroke
 2-5/8 in / 67 mm

 Blows per minute
 3 500

AIR SYSTEM

Air Inlet (NPT)1/4 inMinimum hose size3/8 in / 10 mmAverage air consumption2.90 CFM / 82.1 L/minAir consumption at load2.93 CFM / 82.9 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744) 94.7 / 105.7 dB(A)
Vibration level / measurement uncertainty (ISO28927) 7.5 / 2.8 m/s²

WEIGHT & DIMENSIONS

4.0 lb / 1.8 kg Tool weight Tool dimensions (L x W x H) 10.4 x 2.2 x 6.9 in / 218 x 56 x 175 mm Shipping weight (tool only) 5.3 lb / 2.4 kg Shipping weight (kit) 8.1 lb / 3.7 kg Shipping dimensions (tool only) (L x W x H) 305 x 195 x 80 mm Shipping dimensions (kit) (L x W x H) 445 x 310 x 90 mm UPC / EAN code (tool only) 6 63023 09946 0 UPC / EAN code (kit) 6 63023 09947 7 Origin Made in Taiwan







116-70

03820305

122MAX **ACCESSORIES**



116-K5 03808730



116-66 03820263 Chisel, round shank, 10.2 mm



Chisels, round shank, 10.2 mm (5 pieces)



116-87 03820297 Chisel, round shank, 10.2 mm



116-88 03820271 Chisel, round shank, 10.2 mm

Chisel, round shank, 10.2 mm



116-89 03820289 Chisel, round shank, 10.2 mm



9512 45563749 Quick change retainer

diameter, 30 cm (1 ft)

33104

91486330

77NMC2



IB6NMC2 88103015 IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



88104070 7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)

Hose whip, 1/4" NPT, 6 mm inside



Quick Release Couplings For the complete range, see our accessory catalogue.



Filters, regulators, lubricators For the complete range, see our accessory catalogue.



Lubricants For the complete range, see our accessory catalogue.



10Z4 03875671 Oil, Class 1, no. 10, 0.12 L

www.ingersollrandproducts.com

