

(IR) Ingersoll Rand 88V60P107M-EU

180 mm (7") vertical grinder



Ingersoll Rand Pro-Series grinders and sanders are specially designed for heavy-duty production applications. With their superior power output, they are best suited for big tasks involving heavy material removal in foundries, welding shops, fabrication facilities, steel mills or shipyards.

- Powerful motor delivers 1.56 kW (2.1 HP).
- 6 000 rpm free speed.
- Auto-balancing system significantly reduces vibrations and increases the life of grinding discs, thus increasing user comfort and productivity.
- Internal governor maximizes speed under load, increasing your rate of material removal.
- Built-in mist lubricator automatically oils motor when throttle
- Integral trigger safety lock prevents accidental tool start.
- Optional piped-away exhaust system can further reduce noise level and direct air away from the operator.



Specifications at 6.2 bar (90 psi)

Part Number	88V60P107M-EU
Ordering number	01337948
Wheel type	Type 27
Wheel type	Type 28
Wheel capacity	7 in / 180 mm
Maximum wheel thickness	1/4 in / 6 mm
Spindle size	5/8"-11
Other available versions:	
- 8 500 rpm	88V60P107M-EU

PERFORMANCE

- 230 mm (9") wheel capacity

Rated power 2.1 HP / 1.56 kW Free speed 6 000 rpm

AIR SYSTEM

Air Inlet (NPT) 1/2 in Minimum hose size 3/4 in / 19 mm Air consumption at load 61 CFM / 29.0 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744) 89.2 / 102.2 dB(A) Vibration level / measurement uncertainty (ISO28927) 3.1 / 0.9 m/s²

WEIGHT & DIMENSIONS

Tool weight 8.75 lb / 3.98 kg Height over spindle 6.09 in / 155 mm Shipping weight 11.2 lb / 5.1 kg Shipping dimensions (L x W x H) 290 x 400 x 200 mm UPC / EAN code 6 63024 00357 2 Made in the USA

88V60P109M-EU







Ingersoll Rand 88V60P107M-EU

ACCESSORIES



88V60-K184 03643962

Piped-away exhaust kit



33304

91488205

Hose whip, 1/2" NPT, 13 mm inside diameter, 30 cm (1 ft)



Quick Release Couplings

For the complete range, see our accessory catalogue.



CO-1518

56753122

Hose clamps, 15-18 mm outside diameter, 100 pcs



50P

03875705

Oil, Class 1, no. 50, 0.5 L



IB11NMC4

25014036

IBN/IBS Series nipple, 1/2" male thread, 11 mm bore (ISO6150B / MIL-



RH-12

92536051

PVC hose, 13 mm inside diameter, 30 m



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



88V 88H-TK3

03802915

Motor service kit



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

