



# Hydraulic Breakers



Fisher Offshore supplies a range of medium to heavy duty hydraulic breakers. These units are well balanced for minimum operator fatigue and a feathering valve provides positive control when starting to 'break'. They deliver 1600 to 1100 blows per minute and 34 to 110 foot lbs per blow. Fisher Offshore also supply a variety of breaker steels.

Hydraulic Breakers				
Model	BR37	BR45	BR67	BR87
Capacity	3¼" x 7/8" Hex	1" Parallel Hex	6" x 1¼" Hex	6" x 1¼" Hex
Weight	17kg	26kg	30kg	36kg
Length	570mm	650mm	680mm	680mm
Width	350mm	360mm	400mm	400mm
Pressure	105-140 Bar	105-140 Bar	105-140 Bar	105-140 Bar
Flow Range	26 -34 lpm	26-34 lpm	26-34 lpm	26-34 lpm
Optimum Flow	30 lpm	30lpm	30lpm	30lpm
BPM @ 30 LPM	1600	1800	1300	1000
Porting	½" SAE	½" SAE	½" SAE	½" SAE
Hose Whips	Yes	Yes	Yes	Yes
Connector Size and Type	Aeroquip 5100-12	Aeroquip 5100-12	Aeroquip 5100-12	Aeroquip 5100-12
Hydraulic System	Open Center	Open Center	Open Center	Open Center



For more information on how Fisher Offshore can add value to your offshore operations visit [www.fisheroffshore.com](http://www.fisheroffshore.com)

or contact one of our specialist consultants at [info@fisheroffshore.com](mailto:info@fisheroffshore.com) or call +44 (0) 1651 87 39 32

Fisher Offshore, North Meadows, Oldmeldrum, Aberdeenshire, Scotland AB51 0GQ