

118MAX

Hammer





The 118MAX hammer provides best-in-class power, superior ergonomics and reduced vibration to maximize operator comfort and productivity. It is perfect for exhaust system work, bodyshop applications, scrapping rust, bolt and rivet cutting as well as metal panel cutting.

- Up to 2 500 blows per minute.
- Alloyed steel barrel and heat-treated piston ensures longer life.
- Vibration reduction technology significantly increases user comfort and productivity.
- Quick change retainer provides fast and easy chisel change.
- Rubber handle grip offers great operator comfort and protects from cold air.
- Variable-speed lever allows precise delivery of power and speed.
- 360° swivel inlet helps eliminating twisted hoses.
- Through-handle exhaust directs air away from the operator.
- Tool also available as kit with: quick-change retainer and 5 chisels.

Specifications at 6.2 bar (90 psi)

 Part Number
 118MAX

 Ordering number
 47124490

 Part Number (kit)
 118MAXK

 Ordering number (kit)
 47125877

 Shank type
 round

 Shank size
 0.401 in / 10.2 mm

 Other available versions:
 0.401 in / 10.2 mm

- hexagonal shank 118MAXH
- hexagonal shank and chisels 118MAXHK

PERFORMANCE

 Piston bore
 3/4 in / 19 mm

 Piston stroke
 3-1/2 in / 89 mm

 Blows per minute
 2 500

AIR SYSTEM

Air Inlet (NPT)1/4 inMinimum hose size3/8 in / 10 mmAverage air consumption2.90 CFM / 82.1 L/minAir consumption at load2.98 CFM / 84.4 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)

Vibration level / measurement uncertainty (ISO28927)

94.7 / 105.7 dB(A)

5.7 / 2.3 m/s²

WEIGHT & DIMENSIONS

Tool weight 4.6 lb / 2.1 kg Tool dimensions (L x W x H) 12.4 x 2.2 x 6.9 in / 314 x 56 x 175 mm Shipping weight (tool only) 5.9 lb / 2.7 kg Shipping weight (kit) 8.8 lb / 4.0 kg Shipping dimensions (tool only) (L x W x H) 305 x 195 x 80 mm Shipping dimensions (kit) (L x W x H) 445 x 310 x 90 mm UPC / EAN code (tool only) 6 63023 09948 4 UPC / EAN code (kit) 6 63023 09949 1 Origin Made in Taiwan

 ϵ









116-K5 03808730

Chisels, round shank, 10.2 mm (5 pieces)



116-66

03820263

Chisel, round shank, 10.2 mm



116-70

03820305

Chisel, round shank, 10.2 mm



116-87

03820297

Chisel, round shank, 10.2 mm



116-88

03820271

Chisel, round shank, 10.2 mm



116-89

03820289

Chisel, round shank, 10.2 mm



9512

33104

91486330

45563749

Quick change retainer

diameter, 30 cm (1 ft)



IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)

Hose whip, 1/4" NPT, 6 mm inside



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10Z4

03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

